

In the Claims:

Claims 1-30 (cancelled)

Claim 31 (original): A bow sight, comprising:

a pin guard defining a sight window, said pin guard configured for coupling to a bow
with at least one mounting member;

at least one sight pin coupled to said pin guard and extending into said sight window;

an elongate fiber optic member attached to said at least one sight pin having a first end

and a second end, said first end supported by said at least one sight pin

proximate said first end, said first end forming a sight indicia within said sight

window when viewing a front side of said at least one sight pin; and

a non-electric, luminescent member positioned in proximity to said elongate fiber optic

member along a length thereof to provide illumination thereto in conditions of low
or absent ambient light.

Claim 32 (original): The sight of claim 31, wherein said non-electric, light-emitting
member is selectively positionable to register against said fiber optic member.

Claim 33 (original): The sight of claim 31, wherein said pin guard defines a channel in
an exterior surface thereof, the channel at least partially exposed to ambient light, said
luminescent member disposed within said channel and said elongate fiber optic
member disposed over said luminescent member, extending around a portion of said
exterior surface and at least partially disposed within said channel.

Claim 34 (original) : The sight of claim 33, wherein the luminescent member comprises an elongate segment of tape.

Claim 35 (original): The sight of claim 33, wherein said elongate fiber optic member extends from said first end to said channel.

Claim 36 (original): The sight of claim 35, wherein said non-electric, luminescent member is positioned adjacent a substantial portion of the length of said fiber optic member.

Claims 37-45 (cancelled)

Claim 46 (original): A bow sight, comprising:

a pin guard defining a sight window, said pin guard configured for coupling to a bow

with at least one mounting member, said pin guard defining a channel in an

exterior surface thereof, the channel at least partially exposed to ambient light;

at least one sight pin coupled to said pin guard and extending into said sight window;

and

an elongate fiber optic member attached to said at least one sight pin having a first end

and a second end, said first end supported by said at least one sight pin

proximate said first end, said first end forming a sight indicia when viewing a

front side of said at least one sight pin, and said elongate fiber optic member

disposed at least partially within said channel for light gathering when the pin guard is exposed to light.

Claim 47 (original): The bow sight of claim 46, further comprising a non-electric, luminescent member disposed within said channel and positioned in proximity to said elongate fiber optic member along a length thereof to provide illumination thereto in conditions of low or absent ambient light.

Claim 48 (original): The bow sight of claim 47, wherein , said elongate fiber optic member is disposed over said luminescent member and extends around a portion of said exterior surface at least partially within said channel.

Claim 49 (original) : The sight of claim 47, wherein the luminescent member comprises an elongate segment of tape.

Claim 50 (currently amended): The sight of claim 46, wherein said elongate fiber optic member extends from said first end to a said second end proximate said channel.

Claim 51 (original): The sight of claim 49, wherein said non-electric, luminescent member is positioned adjacent a substantial portion of the length of said fiber optic member disposed within said channel.